

## FILTRATION UNITS

### FILTRATION KIT ORION

Filtration equipment – Filter from polypropylen, complete with internal tubing, inspection windows, drain valve with a reduction to a hose, pressure gauge with de-aeration, 4-or 6-way TOP valve. Assembly with a self-priming plastic pump Infinity HPV , hair preliminary filter, plastic pallet. Operation pressure: 2,5 bar



		Rabat Group
140011	<b>ORION Ø 380</b> Valve: 4 Capacity: 6 m3/h Filter charge: 42 kg Pump - Type: Infinity HPV 33, 0,24 kW/230 V	C
140012	<b>ORION Ø 380</b> Valve: 6 Capacity: 6 m3/h Filter charge: 42 kg Pump - Type: Infinity HPV 33, 0,24 kW/230 V	C
140013	<b>ORION Ø 480</b> Valve: 6 Capacity: 10 m3/h Filter charge: 80 kg Pump - Type: Infinity HPV 50, 0,37 kW/230 V	C
140014	<b>ORION Ø 560</b> Valve: 6 Capacity: 12 m3/h Filter charge: 140 kg Pump - Type: Infinity HPV 75, 0,55 kW/230 V	C

### FILTRATION KIT BALI

This filtr is manufactured in polyetilene hight density. Fitted with pressure gauge. Selector valve with 6 positions: filter, wash, empty and close. Working pressure: 1,5 kg/cm2 Testing pressure: 2 kg/cm2



		Rabat Group
140046	<b>BALI 300</b> Ø 300 Connections: 1½" Valve: 6 Flow: 4m3/h Filter charge: 20 kg Pump 0,18 kW, 1/4 CV Dimensions filter basic plate: 600 x 350 mm	C

### FILTRATION KIT WITHOUT PUMP



		Rabat Group
140050	<b>BALI 300</b> Ø 300 Filter charge: 20 kg Valve: 6 Dimensions filter basic plate: 600 x 350 mm	C
140051	<b>BALI 400</b> Ø 400 Filter charge: 40 kg Valve: 6 Dimensions filter basic plate: 600 x 350 mm	C
140052	<b>TROPICO 500</b> Ø 500 Height: 1000 mm Valve: 6 Dimensions filter basic plate: 630 x 350 mm	C
140053	<b>TROPICO 600</b> Ø 600 Height: 1160 mm Valve: 6 Dimensions filter basic plate: 630 x 350 mm	C

## FILTRATION KIT TROPICO

Tank system equipped with filter, pump, base and filter-pump connections.  
Lid with clamp closing system.  
Fitted with arms and diffuser made from unplasticised. Filter with pressure gauge manual air valve and water drain cock. Base and plumbing.

				Rabat Group	Price in €
140047	<b>TROPICO 400</b>	Ø 400	Connections: 1½"	C	425
	Valve: 6	Height: 730 mm			
	Dimensions filter basic plate: 600 x 350 mm				
	Working pressure: 2 kg/m <sup>2</sup>	Pump: 1/2 CV			
	Testing pressure: 2,5 kg/m <sup>2</sup>				
140048	<b>TROPICO 500</b>	Ø 500	Connections: 1½"	C	473
	Valve: 6	Height: 1000 mm			
	Dimensions filter basic plate: 630 x 350 mm				
	Working pressure: 2 kg/m <sup>2</sup>	Pump: 3/4 CV			
	Testing pressure: 2,5 kg/m <sup>2</sup>				
140049	<b>TROPICO 600</b>	Ø 600	Connections: 1½"	C	538
	Valve: 6	Height: 1160 mm			
	Dimensions filter basic plate: 630 x 350 mm				
	Working pressure: 2 kg/m <sup>2</sup>	Pump: 1 CV			
	Testing pressure: 2,5 kg/m <sup>2</sup>				

## FILTRATION KIT QUICK

Filtration equipment - filter from polypropylen, complete with internal tubing, inspection window, drain valve with a reduction to a hose, pressure gauge with de-aeration, 6-way valve. Assembly with a self-priming plastic pump, hair preliminary filter, plastic pallet.  
Operation pressure: 2,5 bar



				Rabat Group	Price in €
141111	<b>QUICK KIT</b>			C	367,5
	Capacity: 4 m <sup>3</sup> /h		Sand: 42 kg		
	Pump - Type: MICRO 25				
142222	<b>QUICK KIT</b>			C	389,55
	Capacity: 6 m <sup>3</sup> /h		Sand: 42 kg		
	Pump - Type: MICRO 33				
143333	<b>QUICK KIT</b>			C	425,25
	Capacity: 6 m <sup>3</sup> /h		Sand: 42 kg		
	Pump - Type: HPS 33				

## FILTRATION KIT DRACO

Filtration unit - Filter from polyester resin with glass fibre, complete with internal tubing, inspection windows, drain valve with a reduction to a hose, pressure gauge with de-aeration, 6-way valve. Assembly with a plastic pump Infinity MICRO, hair preliminary filter, plastic pallet. Operation pressure: 2,5 bar



				Rabat Group	Price in €
140010	<b>DRACO Ø 450</b>			C	636,7
	Valve: 6	Capacity: 5,5 m <sup>3</sup> /h	Filter charge: 70 kg		
	Pump - Type: Infinity MICRO		0,24 kW/230 V		

## FILTRATION KIT ARA

Filtration equipment - Filter from polyester resin with glass fibre, complete with internal tubing, inspection window, drain valve with a reduction to a hose, pressure gauge with de-aeration, 6-way valve. Assembly with a self-priming plastic pump Infinity HPV, hair preliminary filter, plastic pallet. Operation pressure: 2,5 bar



140004 **ARA Ø 450**  
Valve: 6 Capacity: 7,5 m3/h Filter charge: 70 kg  
Pump - Type: Infinity HPV 33, 0,24 kW/230 V

140005 **ARA Ø 520**  
Valve: 6 Capacity: 10 m3/h Filter charge: 100 kg  
Pump - Type: Infinity HPV 50, 0,37 kW/230 V



140006 **ARA Ø 610**  
Valve: 6 Capacity: 14 m3/h Filter charge: 125 kg  
Pump - Type: Infinity HPV 75, 0,55 kW/230 V

**Rabat Group**

C

C

C

## FILTRATION KIT VELA

Filtration equipment - Filter from polyester resin with glass fibre, complete with internal tubing, inspection window, drain valve with a reduction to a hose, pressure gauge with de-aeration, 6-way valve. Assembly with a self-priming plastic pump Infinity HGV, large hair preliminary filter, plastic pallet. Operation pressure: 2,5 bar



140007 **VELA Ø 520**  
Valve: 6 Capacity: 10 m3/h Filter charge: 100 kg  
Pump - Type: Infinity HGV 50, 0,37 kW/230 V

140008 **VELA Ø 610**  
Valve: 6 Capacity: 14 m3/h Filter charge: 125 kg  
Pump - Type: Infinity HGV 75, 0,55 kW/230 V



140009 **VELA Ø 765**  
Valve: 6 Capacity: 23 m3/h Filter charge: 225 kg  
Pump - Type: Infinity HGV 150, 1,24 kW/230 V

**Rabat Group**

C

C

C

## FILTRATION KIT COMPACT M

Filter units COMPACT - M is high quality, compact filter units for water filtration in swimming pools and whirlpools. Filter unit is set up from: filter from polyester resin with glass fibre, complete with internal tubing, inspection windows, drain valve with reduction to a hose, air relief valve with manometer, manual 6-way valve, assembly with a self-priming plastic pump INFINITY MICRO or HGS, preliminary filter, control unit Pool Control IF with an analogy switching clock and continuous electronic motor protection 0,25-2,25 kW/230 V and 3,0-4,2 kW/400 V, all complete are assembled on plastic pallet.

**Rabat  
Group  
C**

140020 **Compact 450 M** Ø 450 mm Filter height: 690mm  
Capacity: 5 m3/h Power: 0,24 kW Filter charge: 70 kg  
Filtration area: 0,16 m2 Weight without sand: 28 kg  
Max. operation pressure: 2,5 bar Voltage: 230 V/50 Hz  
Pump - Type: MICRO 33  
Filter control units: Pool Control IF  
Dimensions filter basic plate: 630 mm x 400 mm x 35 mm



140021 **Compact 520 M** Ø 520 mm Filter height: 730mm  
Capacity: 7,5 m3/h Power: 0,37 kW Filter charge: 100 kg  
Filtration area: 0,21 m2 Weight without sand: 35 kg  
Max. operation pressure: 2,5 bar Voltage: 230 V/50 Hz  
Pump - Type: MICRO 50  
Filter control units: Pool Control IF  
Dimensions filter basic plate: 630 mm x 400 mm x 35 mm

140022 **Compact 520 M** Ø 520 mm Filter height: 730mm  
Capacity: 10 m3/h Power: 0,37 kW Filter charge: 100 kg  
Filtration area: 0,21 m2 Weight without sand: 40 kg  
Max. operation pressure: 2,5 bar Voltage: 230 V/50 Hz  
Pump - Type: HGS 50  
Filter control units: Pool Control IF  
Dimensions filter basic plate: 630 mm x 400 mm x 35 mm





140023 **Compact 610 M** Ø 610 mm Filter height: 760mm  
Capacity: 14 m3/h Power: 0,55 kW Filter charge: 125 kg  
Filtration area: 0,29 m2 Weight without sand: 47 kg  
Max. operation pressure: 2,5 bar Voltage: 230 V/50 Hz  
Pump - Type: HGS 75  
Filter control units: Pool Control IF  
Dimensions filter basic plate: 800 mm x 500 mm x 35 mm

140024 **Compact 765 M** Ø 765 mm Filter height: 830mm  
Capacity: 23 m3/h Power: 1,1 kW Filter charge: 225 kg  
Filtration area: 0,46 m2 Weight without sand: 64 kg  
Max. operation pressure: 2,5 bar Voltage: 230 V/50 Hz  
Pump - Type: HGS 150  
Filter control units: Pool Control IF  
Dimensions filter basic plate: 1100 mm x 750 mm x 35 mm

## FILTRATION KIT COMPACT A

Filter units COMPACT - A is high quality, compact filter units for water filtration in swimming pools and whirlpools. Filter unit is set up from: filter from polyester resin with glass fibre, complete with internal tubing, inspection windows, drain valve with reduction to a hose, air relief valve with manometer, automatic 6-way valve, assembly with a self-priming plastic pump INFINITY MICRO or HGS, preliminary filter, filter and backwash control unit Eurotronic 20 with an analogy switching clock, all complete are assembled compactly.

				Rabat Group
	140025	<b>Compact 450 A</b> Ø 450 mm Capacity: 5 m <sup>3</sup> /h    Power: 100 W Filtration area: 0,16 m <sup>2</sup> Max. operation pressure: 2,5 bar Pump - Type: MICRO 33 Filter + Backwash control unit Eurotronic 20 Dimensions filter basic plate: 400 mm x 35 mm	Filter height: 690mm Filter charge: 70 kg Weight without sand: 28 kg Voltage: 230 V/50 Hz	C
	140026	<b>Compact 520 A</b> Ø 520 mm Capacity: 7,5 m <sup>3</sup> /h    Power: 100 W Filtration area: 0,21 m <sup>2</sup> Max. operation pressure: 2,5 bar Pump - Type: MICRO 50 Filter + Backwash control unit Eurotronic 20 Dimensions filter basic plate: 400 mm x 35 mm	Filter height: 730mm Filter charge: 100 kg Weight without sand: 35 kg Voltage: 230 V/50 Hz	C
	140027	<b>Compact 520 A</b> Ø 520 mm Capacity: 10 m <sup>3</sup> /h    Power: 100 W Filtration area: 0,21 m <sup>2</sup> Max. operation pressure: 2,5 bar Pump - Type: HGS 50 Filter + Backwash control unit Eurotronic 20 Dimensions filter basic plate: 400 mm x 35 mm	Filter height: 730mm Filter charge: 100 kg Weight without sand: 40 kg Voltage: 230 V/50 Hz	C
	140028	<b>Compact 610 A</b> Ø 610 mm Capacity: 14 m <sup>3</sup> /h    Power: 100 W Filtration area: 0,29 m <sup>2</sup> Max. operation pressure: 2,5 bar Pump - Type: HGS 75 Filter + Backwash control unit Eurotronic 20 Dimensions filter basic plate: 400 mm x 35 mm	Filter height: 760mm Filter charge: 125 kg Weight without sand: 47 kg Voltage: 230 V/50 Hz	C
	140029	<b>Compact 765 A</b> Ø 765 mm Capacity: 23 m <sup>3</sup> /h    Power: 100 W Filtration area: 0,46 m <sup>2</sup> Max. operation pressure: 2,5 bar Pump - Type: HGS 150 Filter + Backwash control unit Eurotronic 20 Dimensions filter basic plate: 400 mm x 35 mm	Filter height: 830mm Filter charge: 225 kg Weight without sand: 64 kg Voltage: 230 V/50 Hz	C

## FILTRATION KIT VELA COMFORT M

Filter units VELA Comfort M is high quality, compact filter units for water filtration in swimming pools and whirlpools.

Filter units VELA Comfort M is set up from: filter from polyester resin with glass fibre, complete with internal tubing, inspection windows, drain valve with reduction to a hose, air relief valve with manometer, manual 6-way valve, assembly with a self-priming plastic pump INFINITY HGS, large high preliminary filter, electric heater D-EWT from stainless-steel, control unit Pool Control IF with an analogy switching clock and continuous electronic motor protection 0,25-2,25 kW/230 V and 3,0-4,2 kW/400 V, all complete are assembled on plastic pallet.

### Rabat Group

140036 **VELA Comfort 520 M** Ø 520 mm Filter height: 730 mm  
 Capacity: 10 m<sup>3</sup>/h Power: 0,37 kW Filter charge: 100 kg  
 Filtration area: 0,21 m<sup>2</sup> Weight without sand: 45 kg  
 Max. operation pressure: 2,5 bar Voltage: 230 V/50 Hz  
 Pump - Type: HGS 50 Electric heater: D-EWT 6  
 Filter control units: Pool Control IF  
 Dimensions filter basic plate: 800 mm x 500 mm x 35 mm



140037 **VELA Comfort 610 M** Ø 610 mm Filter height: 760 mm  
 Capacity: 14 m<sup>3</sup>/h Power: 0,55 kW Filter charge: 125 kg  
 Filtration area: 0,29 m<sup>2</sup> Weight without sand: 52 kg  
 Max. operation pressure: 2,5 bar Voltage: 230 V/50 Hz  
 Pump - Type: HGS 75 Electric heater: D-EWT 9  
 Filter control units: Pool Control IF  
 Dimensions filter basic plate: 1100 mm x 750 mm x 35 mm





140038 **VELA Comfort 765 M** Ø 765 mm Filter height: 830 mm  
 Capacity: 23 m<sup>3</sup>/h Power: 1,1 kW Filter charge: 225 kg  
 Filtration area: 0,46 m<sup>2</sup> Weight without sand: 69 kg  
 Max. operation pressure: 2,5 bar Voltage: 230 V/50 Hz  
 Pump - Type: HGS 150 Electric heater: D-EWT 12  
 Filter control units: Pool Control IF  
 Dimensions filter basic plate: 1100 mm x 750 mm x 35 mm

## FILTRATION KIT VELA COMFORT A

Filter units VELA Comfort A is high quality, compact filter units for water filtration in swimming pools and whirlpools.

Filter units VELA Comfort A is set up from: filter from polyester resin with glass fibre, complete with internal tubing, inspection windows, drain valve with reduction to a hose, air relief valve with manometer, automatic 6-way valve, assembly with a self-priming plastic pump INFINITY HGS, large high preliminary filter, electric heater D-EWT from stainless-steel, control unit Pool Control IF with an analogy switching clock and continuous electronic motor protection 0,25-2,25 kW/230 V and 3,0-4,2 kW/400 V, back wash control unit Eurotronic 10, all complete are assembled on plastic pallet.

### Rabat Group

- |   |  |   |   |   |
|---|--|---|---|---|
| 140039  | <b>VELA Comfort 520 A</b> Ø 520 mm<br>Capacity: 10 m <sup>3</sup> /h    Power: 0,37 kW<br>Filtration area: 0,21 m <sup>2</sup><br>Max. operation pressure: 2,5 bar<br>Pump - Type: HGS 50<br>Filter control units: Pool Control IF<br>Filter + Backwash control units: Eurotronic 10<br>Dimensions filter basic plate: 800 mm x 500 mm x 35 mm | Filter height: 730 mm<br>Filter charge: 100 kg<br>Weight without sand: 45 kg<br>Voltage: 230 V/50 Hz<br>Electric heater: D-EWT 6  | C   |   |
|    | 140040   | <b>VELA Comfort 610 A</b> Ø 610 mm<br>Capacity: 14 m <sup>3</sup> /h    Power: 0,55 kW<br>Filtration area: 0,29 m <sup>2</sup><br>Max. operation pressure: 2,5 bar<br>Pump - Type: HGS 75<br>Filter control units: Pool Control IF<br>Filter + Backwash control units: Eurotronic 10<br>Dimensions filter basic plate: 1100 mm x 750 mm x 35 mm | Filter height: 760 mm<br>Filter charge: 125 kg<br>Weight without sand: 52 kg<br>Voltage: 230 V/50 Hz<br>Electric heater: D-EWT 9  | C |
|  | 140041   | <b>VELA Comfort 765 A</b> Ø 765 mm<br>Capacity: 23 m <sup>3</sup> /h    Power: 1,1 kW<br>Filtration area: 0,46 m <sup>2</sup><br>Max. operation pressure: 2,5 bar<br>Pump - Type: HGS 150<br>Filter control units: Pool Control IF<br>Filter + Backwash control units: Eurotronic 10<br>Dimensions filter basic plate: 1100 mm x 750 mm x 35 mm | Filter height: 830 mm<br>Filter charge: 225 kg<br>Weight without sand: 69 kg<br>Voltage: 230 V/50 Hz<br>Electric heater: D-EWT 12 | C |

## FILTRATION KIT COMFORT M

Filter units Comfort M is high quality, compact filter units for water filtration in swimming pools and whirlpools.

Filter units Comfort M is set up from: filter from polyester resin with glass fibre, complete with internal tubing, inspection windows, drain valve with reduction to a hose, air relief valve with manometer, manual 6-way valve, assembly with a self-priming plastic pump INFINITY HGS, large high preliminary filter, heat exchanger D-HWT 35 plus from stainless-steel, with heating circuit circulations pump, zone valve, control unit Pool Master 230 with an analogy switching clock and temperature control for pool water, all complete are assembled on plastic pallet.

**Rabat  
Group**

140030 **Comfort 520 M** Ø 520 mm Filter height: 730 mm  
 Capacity: 10 m<sup>3</sup>/h Power: 0,37 kW Filter charge: 100 kg  
 Filtration area: 0,21 m<sup>2</sup> Weight without sand: 50 kg  
 Max. operation pressure: 2,5 bar Voltage: 230 V/50 Hz  
 Pump - Type: HGS 50 Heat exchanger: D-HWT 35 plus  
 Filter control units: Pool Master 230 Power: 40 kW 90/70°C  
 Dimensions filter basic plate: 1100 mm x 750 mm x 35 mm



140031 **Comfort 610 M** Ø 610 mm Filter height: 760 mm  
 Capacity: 14 m<sup>3</sup>/h Power: 0,55 kW Filter charge: 125 kg  
 Filtration area: 0,29 m<sup>2</sup> Weight without sand: 57 kg  
 Max. operation pressure: 2,5 bar Voltage: 230 V/50 Hz  
 Pump - Type: HGS 75 Heat exchanger: D-HWT 35 plus  
 Filter control units: Pool Master 230 Power: 40 kW 90/70°C  
 Dimensions filter basic plate: 1100 mm x 750 mm x 35 mm

140032 **Comfort 765 M** Ø 765 mm Filter height: 830 mm  
 Capacity: 23 m<sup>3</sup>/h Power: 1,1 kW Filter charge: 225 kg  
 Filtration area: 0,46 m<sup>2</sup> Weight without sand: 74 kg  
 Max. operation pressure: 2,5 bar Voltage: 230 V/50 Hz  
 Pump - Type: HGS 150 Heat exchanger: D-HWT 35 plus  
 Filter control units: Pool Master 230 Power: 40 kW 90/70°C  
 Dimensions filter basic plate: 1100 mm x 750 mm x 35 mm





## FILTRATION KIT COMFORT A

Filter units Comfort A is high quality, compact filter units for water filtration in swimming pools and whirlpools.

Filter units Comfort A is set up from: filter from polyester resin with glass fibre, complete with internal tubing, inspection windows, drain valve with reduction to a hose, air relief valve with manometer, automatic 6-way valve, assembly with a self-priming plastic pump INFINITY HGS, large high preliminary filter, heat exchanger D-HWT 35 plus from stainless-steel, with heating circuit circulations pump, zone valve, control unit Pool Master 230 with an analogy switching clock and temperature control for pool water, backwash control unit Eurotronic 10, all complete are assembled on plastic pallet.

**Rabat  
Group**



140033 **Comfort 520 A** Ø 520 mm Filter height: 730 mm  
 Capacity: 10 m<sup>3</sup>/h Power: 0,37 kW Filter charge: 100 kg  
 Filtration area: 0,21 m<sup>2</sup> Weight without sand: 51 kg  
 Max. operation pressure: 2,5 bar Voltage: 230 V/50 Hz  
 Pump - Type: HGS 50 Heat exchanger: D-HWT 35 plus  
 Filter control units: Pool Master 230 Power: 40 kW 90/70°C  
 Filter + Backwash control units: Eurotronic 10  
 Dimensions filter basic plate: 1100 mm x 750 mm x 35 mm

C



140034 **Comfort 610 A** Ø 610 mm Filter height: 760 mm  
 Capacity: 14 m<sup>3</sup>/h Power: 0,55 kW Filter charge: 125 kg  
 Filtration area: 0,29 m<sup>2</sup> Weight without sand: 58 kg  
 Max. operation pressure: 2,5 bar Voltage: 230 V/50 Hz  
 Pump - Type: HGS 75 Heat exchanger: D-HWT 35 plus  
 Filter control units: Pool Master 230 Power: 40 kW 90/70°C  
 Filter + Backwash control units: Eurotronic 10  
 Dimensions filter basic plate: 1100 mm x 750 mm x 35 mm

C

140035 **Comfort 765 A** Ø 765 mm Filter height: 830 mm  
 Capacity: 23 m<sup>3</sup>/h Power: 1,1 kW Filter charge: 225 kg  
 Filtration area: 0,46 m<sup>2</sup> Weight without sand: 75 kg  
 Max. operation pressure: 2,5 bar Voltage: 230 V/50 Hz  
 Pump - Type: HGS 150 Heat exchanger: D-HWT 35 plus  
 Filter control units: Pool Master 230 Power: 40 kW 90/70°C  
 Filter + Backwash control units: Eurotronic 10  
 Dimensions filter basic plate: 1100 mm x 750 mm x 35 mm

C

## FILTRATION KIT VIRGO COMFORT M

Filter units VIRGO Comfort M - is high quality, compact multi-bed filter units for water filtration swimming pools and whirlpools.

Filter units VIRGO Comfort M - is set up from: multi-bed filter from polyester resin with glass fibre, complete with internal tubing, inspection windows, drain valve with reduction to a hose, air relief valve with manometer, manual 6-way valve, assembly with a self-priming plastic pump INFINITY HGS, large high preliminary filter, heat exchanger D-HWT 35 plus from stainless - steel, with heating circuit circulations pump, zone valve, control unit Pool control INFINITY M 230V/380V/50Hz with an analogy switching clock, with continuous electronic motor protection 0,25 - 3,5 kW, electronic temperature control for pool water, solar regulation, solar sensor system, all complete are assembled on plastic pallet.



140042 **VIRGO Comfort 610 M** Ø 610 mm Filter height: 1300 mm  
 Capacity: 14 m3/h Power: 0,55 kW Filter charge: 375 kg  
 Filtration area: 0,29 m2 Weight without sand: 79 kg  
 Max. operation pressure: 2,5 bar Voltage: 230 V/50 Hz  
 Pump - Type: HGS 75  
 Filter control units: Pool Control Infinity M  
 Dimensions filter basic plate: 1100 mm x 750 mm x 35 mm

Rabat  
Group  
C



140043 **VIRGO Comfort 765 M** Ø 765 mm Filter height: 1350 mm  
 Capacity: 23 m3/h Power: 1,1 kW Filter charge: 500 kg  
 Filtration area: 0,46 m2 Weight without sand: 94 kg  
 Max. operation pressure: 2,5 bar Voltage: 230 V/50 Hz  
 Pump - Type: HGS 150  
 Filter control units: Pool Control Infinity M  
 Dimensions filter basic plate: 1100 mm x 750 mm x 35 mm

C

## FILTRATION KIT VIRGO COMFORT A

Filter units VIRGO Comfort A - is high quality, compact multi-bed filter units for water filtration swimming pools and whirlpools.

Filter units VIRGO Comfort A - is set up from: multi-bed filter from polyester resin with glass fibre, complete with internal tubing, inspection windows, drain valve with reduction to a hose, air relief valve with manometer, automatic 6-way valve, assembly with a self-priming plastic pump INFINITY HGS, large high preliminary filter, heat exchanger D-HWT 35 plus from stainless - steel, with heating circuit circulations pump, zone valve, control unit Pool control INFINITY A 230V/380V/50Hz with multi-purpose display and foil keyboard, with continuous electronic motor protection 0,25 - 3,5 kW, electronic temperature control for pool water, solar regulation, solar sensor system, backwash control unit Euromatic, all complete are assembled on plastic pallet.



140044 **VIRGO Comfort 610 A** Ø 610 mm Filter height: 1300 mm  
 Capacity: 14 m3/h Power: 0,55 kW Filter charge: 375 kg  
 Filtration area: 0,29 m2 Weight without sand: 80 kg  
 Max. operation pressure: 2,5 bar Voltage: 230 V/50 Hz  
 Pump - Type: HGS 75  
 Filter control units: Pool Control Infinity A  
 Filter + Backwash control units: Euromatic  
 Dimensions filter basic plate: 1100 mm x 750 mm x 35 mm

Rabat  
Group  
C



140045 **VIRGO Comfort 765 A** Ø 765 mm Filter height: 1350 mm  
 Capacity: 23 m3/h Power: 1,1 kW Filter charge: 500 kg  
 Filtration area: 0,46 m2 Weight without sand: 95 kg  
 Max. operation pressure: 2,5 bar Voltage: 230 V/50 Hz  
 Pump - Type: HGS 150  
 Filter control units: Pool Control Infinity A  
 Filter + Backwash control units: Euromatic  
 Dimensions filter basic plate: 1100 mm x 750 mm x 35 mm

C